DU084

D400 (Group 4)



Ductile iron access covers, suitable for use in areas where cars and lorries have access, including carriageways, hard shoulders and pedestrian zones. Capable of withstanding a 400kN (40 tonnes) test load.

OPTIONAL EXTRAS

- Badged 0
- Locked 0
- Vented 0
- **Sealing Plate** 0

PRODUCT CODE	DU084	BASE SIZE	830mm x 830mm
CLEAR OPENING	675mm x 675mm	DEPTH	150mm

FEATURES

	SMARTGRIP TECHNOLOGY™ Unique pattern design provides a PSRV value of >70 (UKAS Accredited 3rd Party).	<u></u>	INCREASED BEDDING AREA Designed with a large flange for increased bedding area and decreased frame bearing pressure that meet the requirements of CD534,	
V	KITEMARK		BS7903:2020.	
	Exceeds the requirements of BS EN124-2:2015, tested and certified by BSI.		DEPTH OF INSERTION	
\ominus	THREE POINT SUSPENSION		Meets the depth of insertion requirements of BS EN124-2:2015, CD534	
	Three point suspension for non-rock stability.		and BS7903.	
<u></u>	RATIO	мсню	COMPLIES WITH MCHW	
	Ductile iron for improved weight to strength ratio.		Manual for Contract Highway Works, Series 500.	
	COATING	DMRB	COMPLIES WITH DMRB	
<u> </u>	Black coated finish.		Meets the requirements of Highways England specification CD534.	
S	STRONG & DURABLE		RECYCLABLE	
	Spheroidal graphite cast iron according to EN 1563:2018, as per the		Long life asset with high circularity contributing to the reduction in	
	requirements of BS EN124-2:2015.		carbon footprint.	



+44 (0)1922 613 222

enquiries@ecclesproducts.com www.ecclesproducts.com Eccles (UK Foundries FE) Limited Portland Street, Walsall,

KITEMAR KM 656300 BS EN124-2:2015

Ductile Iron Access Cover

DU084 675x675x150

West Midlands, WS2 8AA, UK

DU084

D400 (Group 4)

Ductile Iron Access Cover

DU084 675x675x150



Ductile iron access covers, suitable for use in areas where cars and lorries have access, including carriageways, hard shoulders and pedestrian zones. Capable of withstanding a 400kN (40 tonnes) test load.



DATA

Dimensions

A / Base Size: 830mm x 830mm

B / Clear Opening: 675mm x 675mm

C / Depth: 150mm

Materials

Ductile Iron

Finish

Black Coated

Certification

BSI Kitemark

Standard

EN124-2:2015

Product Type

Ductile Iron Access Cover



Disclaimer: Eccles (UK Foundries FE) Ltd are continually seeking to improve our products and we therefore reserve the right to alter product specifications without prior notice. It is the responsibility of all users to ensure that the above product data is current. Installation details are available on request. It is always recommended that the use of road plates be used where access covers, gully grates and frames are exposed to construction and site traffic during the construction phase of any project and in accordance with "Annex F" EN124-1:2015.



+44 (0)1922 613 222

enquiries@ecclesproducts.com www.ecclesproducts.com

Eccles (UK Foundries FE) Limited Portland Street, Walsall, West Midlands, WS2 8AA, UK



830 675 VILOS XILOS VILANA VILOS VILOS VILANA VILOS VILO

