# **DU086**

### **D400 (Group 4)**



Ductile iron access covers, suitable for use in areas where cars and lorries have access, including carriageways, hard shoulders and pedestrian zones. Capable of withstanding a 400kN (40 tonnes) test load.

# MaxiGrip



### **OPTIONAL EXTRAS**

- Badged 0
- Locked 0
- Vented •
- **Sealing Plate** Ö

PRODUCT CODE	DU086	BASE SIZE	1050mm x 750mm
CLEAR OPENING	900mm x 600mm	DEPTH	150mm

### **FEATURES**

	SMARTGRIP TECHNOLOGY™ Unique pattern design provides a PSRV value of >70 (UKAS Accredited 3rd Party). KITEMARK	Ļ	INCREASED BEDDING AREA Designed with a large flange for increased bedding area and decreased frame bearing pressure that meet the requirements of CD534, BS7903:2020.
	Exceeds the requirements of BS EN124-2:2015, tested and certified by BSI.		DEPTH OF INSERTION
$\bigotimes$	THREE POINT SUSPENSION Three point suspension for non-rock stability.		Meets the depth of insertion requirements of BS EN124-2:2015, CD534 and BS7903.
<u></u>	RATIO Ductile iron for improved weight to strength ratio.	мсни	COMPLIES WITH MCHW Manual for Contract Highway Works, Series 500.
<u>«</u>	COATING Black coated finish.	DMRB	<b>COMPLIES WITH DMRB</b> Meets the requirements of Highways England specification CD534.
٩	<b>STRONG &amp; DURABLE</b> Spheroidal graphite cast iron according to EN 1563:2018, as per the requirements of BS EN124-2:2015.		<b>RECYCLABLE</b> Long life asset with high circularity contributing to the reduction in carbon footprint.



### +44 (0)1922 613 222

enquiries@ecclesproducts.com www.ecclesproducts.com Eccles (UK Foundries FE) Limited Portland Street, Walsall,

West Midlands, WS2 8AA, UK

KITEMARI KM 656300 RS FN124-2:201

# Ductile Iron Access Cover

## DU086 900x600x150

# **DU086**

### D400 (Group 4)

# Ductile Iron Access Cover

# DU086 900x600x150



Ductile iron access covers, suitable for use in areas where cars and lorries have access, including carriageways, hard shoulders and pedestrian zones. Capable of withstanding a 400kN (40 tonnes) test load.



### DATA

#### **Dimensions**

- A / Base Size: 1050mm x 750mm B / Clear Opening: 900mm x 600mm
- **C** / Depth: 150mm

#### **Materials**

Ductile Iron

### Finish

**Black Coated** 

### Certification

**BSI Kitemark** 

### Standard

EN124-2:2015

### **Product Type**

**Ductile Iron Access Cover** 



Disclaimer: Eccles (UK Foundries FE) Ltd are continually seeking to improve our products and we therefore reserve the right to alter product specifications without prior notice. It is the responsibility of all users to ensure that the above product data is current. Installation details are available on request. It is always recommended that the use of road plates be used where access covers, gully grates and frames are exposed to construction and site traffic during the construction phase of any project and in accordance with "Annex F" EN124-1:2015.



### +44 (0)1922 613 222

50

**DIAGRAM KEY** 

enquiries@ecclesproducts.com www.ecclesproducts.com

Eccles (UK Foundries FE) Limited Portland Street, Walsall, West Midlands, WS2 8AA, UK

B

C

**Overall Base** 

**Clear Opening** 

**BASE SIZE** 

**CLEAR OPENING** 

**FRAME DEPTH** 



**Overall Frame** 

